



DESTINY

Multi-purpose Multicat

The Destiny is ideally for port and coastal work such as; lifting, pushing, towing, diving, anchoring, pipelining and crewing. The boat has a stable work platform and a movable wheelhouse. What makes it special are the optional tracks on the side.

Exploitation

| | |
|------------------------|--|
| Name: | Destiny |
| Type: | Shallow drafted multi-purpose multicat |
| Classification: | 20 nM BV 24/7 |
| Flag: | Dutch (NL) |
| Owner: | KW Trans Shipping BV |

Dimensions

| | |
|--------------------------|----------------------------|
| Clear deck space: | approx. 150 m ² |
| Length: | 23,50 m |
| Beam: | 11,45 m |
| Depth: | min. 0,70 m |
| Height: | 4,00-10,00 m |

Bunkering

| | |
|---------------------|-------------------------|
| Gas oil: | cap. 23 m ³ |
| Fresh water: | cap. 25 m ³ |
| Dirty oil: | cap. 1,5 m ³ |
| Sewage: | 500 L |

Performance

| | |
|-----------------------------|---------------------------------|
| Speed approx: | 10 knots |
| Propulsion: | 2x2700 HD 6950 HD |
| Main engines: | Volvo Penta Tier 3 (stage V) |
| Total output: | 1000 BHP Accu pakket 300/600 KW |
| Generator sets: | 30 kVa S4S |
| Pushing capacity: | ca. 3000 m ³ |
| 10 ton Bollard Pull: | Duw 300 m ³ |

Navigation equipment

| | |
|----------------------|-----|
| Radar system: | Yes |
| Echo Sounder: | Yes |
| AIS: | Yes |

Deck equipment

| | |
|-----------------------------|-----------------------------|
| Towing/Anchor Winch: | 2x 50 tons |
| Deck Crane: | 1x140 tm. 6S 5600 kg at 19m |

Moon pool (serveying)

| | |
|-----------------|--------|
| Breadth: | 550 mm |
| Length: | 760 mm |

Accommodation

Comfortable accommodation for 12 persons. All cabins are heated and air-conditioned 6x2 persons. All nautical equipment is available on board.

| Fixed Hool Use | | | Heila HLRM 140 6S | | | | |
|----------------------|--------|--------|-------------------|-------|-------|-------|-------|
| M | 6.28 | 8.35 | 10.42 | 12.48 | 14.6 | 16.82 | 19.03 |
| KG | 19,700 | 14,450 | 11,350 | 9,350 | 7,800 | 6,550 | 5,650 |
| Single line pull use | | | | | | | |
| M | 5.80 | 7.76 | 9.94 | 12.00 | 14.12 | 16.34 | 18.54 |
| KG | 4000 | 4000 | 4000 | 4000 | 4000 | 4000 | 4000 |
| Double line pull use | | | | | | | |
| M | 5.96 | 8.02 | 10.09 | 12.16 | 14.28 | 16.50 | 18.70 |
| KG | 8000 | 8000 | 8000 | 8000 | 7800* | 6550* | 5650* |

